



HAYAN PETROLEUM COMPANY

Fax

To	Respected Bidder
From	HPC
Phone	319 07 299
Fax	314 67 48
Ref.	461/0719/Proc/Ch
Date	11/07/2019
Number of pages	01 (Including this one)+CFT Package (available on website hpc.com.sy)

**Subject: Second C.F.T for supplying of Spare Parts for Control Valves used at GTP & SGS
Jihar. HPC-006/INS/Field/Proc/19
Technical Clarification before Bidding**

Dear Sirs:

Following to the a/m HPC's CFT , and in reply to one of Respected Bidders

Please be informed that the following :

Bidder' S clarifications :

- 1- Provide us with software copy of the tender book and technical attachments .
- 2- For group 1 , advise us the serial number of the valves for which parts intended to use
- 3- For group 2, provide Tag Plate photograph for items 1 to 12 .
- 4- For group 3 , item 1 , provide the serial number of valve .
- 5- For group 3 , item 2 , check attached catalog and choose the right code .

HPC' s reply :

- 1- The software copy is available on website hpc.com.sy .
- 2- Bidder to stick with the part numbers provided as there are no serial numbers available .

3-

Attachment 1

Type	530D
SN :	520045V6P1/09
Body	4"
Trim	2"
Rated pressure/ Temperature	94 Bar (G) / -46 To 87 °C
Pressure CLASS DES	ASME 900
Body Mat'L	ASTM A351 GR CF3M
Packing	GRAFOIL
TrimMaterial	316LSS.STELLITED
Plug Char	LINEAR
Travel / CV	3.6" / 20.5
Spring Rang	8 – 32 PSIG
DiaphragmMaterial	NYLON & NITRILE
SupplyFailure Valve	CLOSES
TAG NO	PV-3102-04A

Attachment 2

Type	530D
SN :	520045V2P1/09
Body	6"
Trim	2.5"
Rated pressure/ Temperature	93 Bar (G) / -46 To 88°C
Pressure CLASS DES	ASME 900
BodyMat'l	ASTM A351 GR CF3M
Packing	GRAFOIL
TrimMaterial	316LSS.STELLITED
Plug Char	LINEAR
Travel / CV	3.6" / 42.3
Spring Rang	8 – 32 PSIG
DiaphragmMaterial	NYLON & NITRILE
SupplyFailure Valve	CLOSES
TAG NO	PV-2102-03A

Attachment 3:

Type	530D
SN :	520045V3P1/09
Body	8"
Trim	5"
Rated pressure/ Temperature	93 Bar (G) / -42 To 82°C
Pressure CLASS DES	ASME 900
Body Mat'l	CF3
Packing	GRAFOIL
TrimMaterial	316LSSSTELLITED
Plug Char	LINEAR
Travel / CV	6" / 78
Spring Rang	20 – 40 PSIG
DiaphragmMaterial	NYLON & NITRILE
SupplyFailure Valve	CLOSES
TAG NO	PV-2501-36B

Attachment 4

Type	AB4001/Butterfly
SN :	520045V8P1/09
Body	8"
Rated pressure/ Temperature	93 Bar (G) / -40 To 82°C
Pressure CLASS DES	ANSI 900
Body Mat'l	ASTM A351 CF3M
Packing	GRAFOIL
TrimMaterial	ASTM A351 GR CF3M
Plug Char	MOD EQ%
Travel / CV	8 - 90° / 1445
Spring Rang	8 - 32 PSIG
DiaphragmMaterial	NYLON & NITRILE
SupplyFailure Valve	CLOSES
TAG NO	PV-2501-41

Attachment 5

Type	AB 4001/Butterfly
SN :	520045V1P1/09
Body	10"
Rated pressure/ Temperature	48Bar (G) / - 70 To 82°C
Pressure CLASS DES	ANSI 600
Body Mat'l	ASTM A351 CF3M
Packing	GRAFOIL
TrimMaterial	ASTM A351 GR CF3M
Plug Char	MOD EQ%
Travel / CV	0-90° / 2850
Spring Rang	8 - 32 PSIG
DiaphragmMaterial	NYLON & NITRILE
SupplyFailure Valve	OPENS
TAG NO	HV-2502-01

4-Bidder to stick with the part numbers provided as there are no serial numbers available.

5-The Right Code is: TZIDC- part no: V18345-1021151001 (M5).

Best Regards,

Chairman

Eng. Ibrahim Ali


